



Elfiq Networks Link Balancer Detailed Product Matrix - End of Sale Models

[End of sale \(product is supported for 5 years after this date\)](#)

	June 1st 2008	June 1st 2008	TBA	Sept. 1st 2010	Nov. 1st 2008	June 30th 2010	Dec. 20th 2010
Performance	LB-500	LB-1000	LB-1100E	LB-1500E	LB-2000	LB-3000	LB-4000E
Incoming and outgoing traffic balancing	✓	✓	✓	✓	✓	✓	✓
Number of ISP links*	2	4	6	6	16	160	320
Throughput (half duplex)*	20Mbps	45 Mbps	75 Mbps	90 Mbps	135 Mbps	800 Mbps total or 500 Mbps per VFI	1.2 Gbps total or 750 Mbps per VFI
Throughput (Full duplex)*	40 Mbps	90 Mbps	150 Mbps	180 Mbps	270 Mbps	1,6 Gbps	2.4 Gbps
Number of sessions*	32 000	64 000	64 000	384 000	256 000	1 536 000	5 120 000
Number of new sessions per second*	12 000	12 000	12 000	15 000	15 000	30 000	50 000
Maximum number of Virtual Balancers (VFI)	1	1	1	1	1	2	5
Number of links per VFI	2	4	6	6	8	32	64
Number of sessions (one VFI loaded)	32 000	64 000	64 000	384 000	128 000	1 024 000	2 048 000
Ethernet Bonding support				✓	✓	✓	✓
Ethernet Bonding maximum throughput (Full duplex)							4Gbps
Balancing	LB-500	LB-1000	LB-1100E	LB-1500E	LB-2000	LB-3000	LB-4000E
OSI model Layer 2 operation (inline unit)	✓	✓	✓	✓	✓	✓	✓
Number of networks (subnets) per link	1	4	4	16	16	64	64
Number of IDNS records (Intelligent DNS)	256	256	256	1024	4096	65536	65536
Persistent session management	✓	✓	✓	✓	✓	✓	✓
Real time balancing mode	NAT / PREF	NAT / TAG / PREF	NAT / TAG / PREF	NAT / TAG / PREF	NAT / TAG / PREF	NAT / TAG / PREF	NAT / TAG / PREF
Traffic segmentation	✓	✓	✓	✓	✓	✓	✓
Quality of Service (QoS) rules	32	32	32	64	64	128	256
Internet Service Verificator	-	✓	✓	✓	✓	✓	✓
Time of Day conditions	-	✓	✓	✓	✓	✓	✓
Intelligent Condition Verificator	-	✓	✓	✓	✓	✓	✓
Uptime and high availability	LB-500	LB-1000	LB-1100E	LB-1500E	LB-2000	LB-3000	LB-4000E
Watchdog timer	✓	✓	✓	✓	✓	✓	✓
LAN Failsafe support	-	-	Hardware	Hardware	-	Programmable 2 pairs	Programmable 3 pairs
High availability support	-	-	✓	✓	✓	✓	✓
Session guard (DoS protection)	✓	✓	✓	✓	✓	✓	✓
Multimode support	-	✓	✓	✓	✓	✓	✓
SitePathMTPX Resilience	LB-500	LB-1000	LB-1100E	LB-1500E	LB-2000	LB-3000	LB-4000E
SitePathMTPX support	-	✓	✓	✓	✓	✓	✓
SitePath AES128 encryption	-	✓	✓	✓	✓	✓	✓
Maximum number of site paths	-	4	16	32	64	256	512
Maximum number of site path groups	-	1	2	8	16	64	128



Elfiq Networks Link Balancer Detailed Product Matrix - End of Sale Models

Geolink Geographic balancing	LB-500	LB-1000	LB-1100E	LB-1500E	LB-2000	LB-3000	LB-4000E
Geolink option	-	-	-	✓	✓	✓	✓
Geolink mode	-	-	-	Inbound	Global and Inbound	Global and Inbound	Global and Inbound
Maximum number of remote sites	-	-	-	2	2	4	4
Networking features	LB-500	LB-1000	LB-1100E	LB-1500E	LB-2000	LB-3000	LB-4000E
DHCP and PPPoE support	✓	✓	✓	✓	✓	✓	✓
Dynamic MTU/MSS support	✓	✓	✓	✓	✓	✓	✓
802.1Q (vlan) support	-	✓	✓	✓	✓	✓	✓
Real time filtering (shunning)	-	✓	✓	✓	✓	✓	✓
Built-in probe	✓	✓	✓	✓	✓	✓	✓
NAT, Block NAT, NAT Masquerading, and PAT support	✓	✓	✓	✓	✓	✓	✓
Management	LB-500	LB-1000	LB-1100E	LB-1500E	LB-2000	LB-3000	LB-4000E
Web-based management and reporting	✓	✓	✓	✓	✓	✓	✓
Console command line interface (CLI)	✓	✓	✓	✓	✓	✓	✓
Alert support (syslog, SMTP, SNMP)	✓	✓	✓	✓	✓	✓	✓
Secure remote access	✓	✓	✓	✓	✓	✓	✓
XML based external API	✓	✓	✓	✓	✓	✓	✓
SNMP MIB II support	✓	✓	✓	✓	✓	✓	✓
Dedicated management port	✓	✓	✓	✓	✓	✓	✓
Physical specifications	LB-500	LB-1000	LB-1100E	LB-1500E	LB-2000	LB-3000	LB-4000E
Speed of network interfaces (Mbps)	10 / 100	10 / 100	10 / 100	10 / 100	10 / 100	10 / 100 / 1000	10 / 100 / 1000
Total number of Ethernet interfaces	4	4	4	4	4	8	10
Number of Gigabit interfaces	0	0	0	0	0	4	8 Copper, 2 SFP
Format	Tabletop	Tabletop	Rackmount 1U	Rackmount 1U	Rackmount 1U	Rackmount 1U	Rackmount 1U
Automatic backup of configuration on Flash	✓	✓	✓	✓	✓	✓	✓
No moving parts design	✓	✓	✓	✓	Fan only	Fan only	Fan only
LCD Display	-	-	-	-	✓	✓	✓
Power requirements	100~240V @ 50~60Hz	100~240V @ 50~60Hz	100~240V @ 50~60Hz	100~240V @ 50~60Hz	100~240V @ 50~60Hz	100~240V @ 50~60Hz	100~240V @ 50~60Hz
	50W	50W	25W	25W	150W	250W	350W
Operating temperature	0 °C to 40 °C	0 °C to 40 °C	0 °C to 40 °C	0 °C to 40 °C	0 °C to 40 °C	0 °C to 40 °C	0 °C to 40 °C
Certifications	CE / FCC / RoHS	CE / FCC / RoHS	CE / FCC / RoHS	CE / FCC / RoHS	CE / FCC / RoHS	CE / FCC / RoHS	CE / FCC / RoHS
Size - L, W, H (inches)	8.25 x 6 x 12	8.25 x 6 x 12	10,75 x 7 x 1,7	16,8 x 9 x 1,7	16,8 x 9 x 1,7	16,8 x 15 x 1,7	16,8 x 18 x 1,7
Hardware warranty	12 months	12 months	12 months	12 months	12 months	12 months	12 months

*: Includes the total capacity of all Virtual Forwarding Interfaces (VFIs)